

# Intuitive handling for secure data.



Discover our software now at  
[testo.com.au!](http://testo.com.au)



## Practical and useful accessories.

Optimise your workflow with Testo's sophisticated and practical accessories – for easy and safe handling in every application.

Accessories	Order no.
<b>Lithium battery CR2032 button cell</b> for reordering (Please order 2 batteries per data logger)	0515 5174
<b>ComSoft Basic</b> Basic software for programming and reading out Testo data loggers including display of measured values in graph and chart form as well as export function (Free download available after registration)	0572 0580
<b>ComSoft Professional</b> Professional software for programming and reading out Testo data loggers and for data archiving with evaluation and display options that go beyond the basic functions	0554 1704
<b>ISO calibration certificate for temperature</b> Calibration points: -18 °C, 0°C, +40 °C (per channel/instrument)	0520 0153
<b>ISO calibration certificate for humidity</b> Calibration points: 11.3 %, 75.3 % relative humidity at +25 °C	0520 0076

Information and further accessories at [testo.com.au](http://testo.com.au)



[testo.com.au](http://testo.com.au)

Be sure. **testo**



**Save time. Cut costs.  
In every measurement environment.**

Optimally air-conditioned rooms and perfectly tempered goods: the testo 174 mini data loggers.

## Precise measurement and seamless documentation.



Download the **testo Smart App** now and use all the benefits!



## Perfect temperatures for maximum product safety.

The intelligent mini data loggers testo 174 with Bluetooth® make monitoring temperature-controlled goods and products safer, more efficient and more convenient than ever before. Intuitive operation, precise measurement, seamless documentation and easy traceability of all measurement values via the free testo Smart App ensure perfect quality management.

**Both mini data loggers with Bluetooth® are HACCP certified, the testo 174 T BT also fulfills the requirements of EN 12830 and is NSF certified. Both instruments therefore guarantee maximum product safety. The seamless connection to the testo Smart App guarantees easy handling even for less experienced or frequently changing personnel.**

With seamless measurement data acquisition and documentation, the testo 174 H BT and testo 174 T BT ensure maximum safety and simplified processes – thanks to Bluetooth® and seamless app connection.

- Precise indoor measurement in the temperature measuring range from -20 °C to +70 °C (testo 174 H BT) or from -30 °C to +70 °C (testo 174 T BT)
- Simple data evaluation via Bluetooth® directly at the measuring point up to a distance of 30 meters
- Reliable automatic data backup when the battery is empty or when changing the battery
- Seamless connection to the free testo Smart App including export function and report generation in PDF format



- ✓ Simple and intuitive configuration and analysis of measurement data via mobile device with the testo Smart App
- ✓ More efficient processes and noticeable time savings by leaving the data logger at the measuring location
- ✓ Fast recording as well as error-free and seamless digital documentation of all measurement results
- ✓ Time-saving and intuitive data acquisition and read-out via USB-C without a separate readout station
- ✓ Seamless continued use of the proven readout procedures and the established PC software
- ✓ Uncomplicated option for combining previous and new USB device versions



## Optimally air-conditioned rooms thanks to reliable monitoring.

With their handy dimensions and a large temperature measurement range, the testo 174 mini data loggers with USB-C are perfect for reliably monitoring your indoor climate to safeguard temperature- and humidity-sensitive goods and products. By eliminating the separate readout station and continuing to use the tried-and-tested PC software, your quality assurance becomes child's play.

**By fulfilling the requirements of HACCP and additionally those of EN 12830 and NSF certification for the testo 174 T, both mini data loggers with USB-C guarantee maximum product safety. The connection to the free software ComSoft Basic ensures smooth processes and makes internal verification management simple, efficient and reliable.**

The testo 174 H and testo 174 T reliably monitor and analyse whether the humidity and temperature in the storage of sensitive goods are within the optimum range – with guaranteed data security.

- Professional software with Excel export function for programming the logger, analysing data and creating reports in PDF format
- Wide temperature measuring range from -20 °C to +70 °C (testo 174 H) or from -30 °C to +70 °C (testo 174 T) for precise indoor measurement
- Reliable automatic data backup when the battery is empty or when changing the battery
- Convenient measurement data storage for up to 16,000 readings

