


[www.testo.com/manuals](http://www.testo.com/manuals)

<https://qr.testo.com/ldtw8z>

[www.saveris.testo.com/get-started](http://www.saveris.testo.com/get-started)












<p><b>testo 160 T:</b> 76 x 64 x 25 mm 3 x 3 x 1 in</p> <p><b>testo 160 TH / testo 160 E:</b> 76 x 64 x 22 mm 3 x 3 x 0.9 in</p>	<p>testo 160 T: -30 ... +50 °C -22 ... +122 °F</p> <p>testo 160 TH / testo 160 E: -10 ... +50 °C +14 ... +122 °F</p> <p>testo 160 T: -30 ... +60 °C -22 ... +140 °F</p> <p>testo 160 TH / testo 160 E: -20 ... +50 °C -4 ... +122 °F</p>	<p>4x AAA alkaline 1.5V 1.5 years</p>	<p>testo 160 T: 0.1 °C 0.1 °F</p> <p>testo 160 TH: 0.1 °C 0.1 °F 0.1 %RH</p> <p>testo 160 E: ① ② ③</p>	<p>testo 160 T: -30 ... +50 °C -22 ... +122 °F</p> <p>testo 160 TH: -10 ... +50 °C +14 ... +122 °F 0 ... 100 % RH</p> <p>testo 160 E: ① ② ③</p>	<p>testo 160 T: ± 0.5 °C (-30 ... +50 °C) ± 0.9 °F (-22 ... +122 °F)</p> <p>testo 160 TH: ± 0.5 °C (-10 ... +50 °C) ± 0.9 °F (+14 ... +122 °F) ± 2 %RH @ +25 °C / 77 °F &amp; 20 ... 80 %RH</p> <p>testo 160 E: ± 3 %RH @ +25 °C / 77 °F &amp; &lt; 20 %RH &amp; &gt; 80 %RH ± 1 %RH hysteresis ± 1 %RH/year drift</p> <p>testo 160 E: ① ② ③</p>	<p>testo 160 T: 107g IP 65 3.8 oz</p> <p>testo 160 TH: 94g IP 20 3.3 oz</p> <p>testo 160 E: 96g IP 20 3.4 oz</p>

# Approval and Certification

<b>Product</b>	WLAN Data Logger
<b>Model No.</b>	testo 160 T testo 160 TH testo 160 E
<b>Order No.</b>	0572 2019 0572 2021 0572 2022
<b>Date</b>	10.01.2025

**i** The use of the wireless module is subject to the regulations and stipulations of the respective country of use, and the module may only be used in countries for which a country certification has been granted. The user and every owner has the obligation to adhere to these regulations and prerequisites for use, and acknowledges that the re-sale, export, import etc. in particular in countries without wireless permits, is his responsibility.

Country	Comments
<b>Australia &amp; New Zealand</b>	 E 1561
<b>Brazil</b>	testo 160 TH:  00844-18-04701 testo 160 E:  01829-18-04701 See Brazil Information
<b>Canada</b>	testo 160 T: IC: 6127B-05722019 testo 160 TH & testo 160 E: IC: 6127B-0572202X Contains IC:21461-LSD4WF0459 See IC Warnings
<b>China</b>	testo 160 TH: CMIIT ID: 2017DJ4557 testo 160 E: CMIIT ID: 2017DJ4559
<b>Europa + EFTA</b>	 <b>i</b> Hereby, Testo SE & Co. KGaA declares that the radio equipment type testo 160 T, testo 160 TH and testo 160 E are in compliance with Directive 2014/53/EU. The full text of the EU declaration of conformity is available at the following internet address: <a href="https://www.testo.com/eu-conformity">https://www.testo.com/eu-conformity</a> <b>EU countries:</b> Belgium (BE), Bulgaria (BG), Denmark (DK), Germany (DE), Estonia (EE), Finland (FI), France (FR), Greece (GR), Ireland (IE), Italy (IT), Latvia (LV), Lithuania (LT), Luxembourg (LU), Malta (MT), Netherlands (NL), Austria (AT), Poland (PL), Portugal (PT), Romania (RO), Sweden (SE), Slovakia (SK), Slovenia (SI), Spain (ES), Czech Republic (CZ), Hungary (HU), Republic of Cyprus (CY). <b>EFTA countries:</b> Iceland, Liechtenstein, Norway, Switzerland  WEEE Reg. no.: DE 75334352
<b>Japan</b>	WLAN module:  R 211-160704 See Japan information
<b>Pakistan</b>	testo 160 TH & testo 160 E: Authorized
<b>Korea</b>	 testo 160 TH: R-CRM-te2-05722021 See KCC Warning
<b>Türkiye</b>	Authorized
<b>United Arab Emirates</b>	testo 160 TH & testo 160 E: Authorization Number: ER57487/17
<b>United Kingdom (UK)</b>	 <b>i</b> The UK Declaration of Conformity can be found on the testo homepage <a href="http://www.testo.com">www.testo.com</a> under the product specific downloads.
<b>USA</b>	 For testo 160 T: FCC ID: WAF-05722019 For testo 160 TH & testo 160 E: FCC ID: WAF-0572202X Contains FCC ID: N8NLS4WF0459 See FCC Warnings

WLAN Information	Feature 特征与参数	Values 数值
	WLAN range / 范围	up to 100 m (328 feet) (free field / 无障碍场地)
	WLAN type / 型号	LSD4WF0459-01D0
	Radio type / 类型	Accord with the standard of IEEE 802.11b/g/n
	Company / 制造商	Lierda Science & Technology Group Co., Ltd
	RF Band / 射频频段	2412 – 2472 MHz
	Power output / 输出功率	13.42 dBm

## IC Warnings

### CAN ICES-003(B) / NMB-003(B)

This Class B digital apparatus complies with Canadian ICES-003.

Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada.

### RSS-Gen & RSS-247 statement

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s).

Operation is subject to the following two conditions:

- (1) this device may not cause interference, and
- (2) this device must accept any interference, including interference that may cause undesired operation of the device.

L'émetteur/récepteur exempt de licence contenu dans le présent appareil est conforme aux CNR d'Innovation, Sciences et Développement économique Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes:

- (1) L'appareil ne doit pas produire de brouillage.
- (2) L'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

### Caution: Radio Frequency Radiation Exposure

This equipment complies with radio frequency exposure limits set forth by the Innovation, Science and Economic Development Canada for an uncontrolled environment.

This equipment should be installed and operated with a minimum distance of 20 cm between the device and the user or bystanders.

### Co-Location

This device must not be co-located or operated in conjunction with any other antenna or transmitter.

### Attention : exposition au rayonnement de radiofréquences

Ce dispositif a été testé pour la conformité avec les valeurs Cet équipement est conforme aux limites d'exposition aux radiofréquences définies par la Innovation, Sciences et Développement économique Canada pour un environnement non contrôlé.

Cet équipement doit être installé et utilisé avec un minimum de 20 cm de distance entre le dispositif et l'utilisateur ou des tiers

### Co-location

Ce dispositif ne doit pas être utilisé à proximité d'une autre antenne ou d'un autre émetteur.

## FCC Warnings

Information from the FCC (Federal Communications Commission)

### For your own safety

Shielded cables should be used for a composite interface. This is to ensure continued protection against radio frequency interference.

### FCC warning statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

### Caution

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. Shielded interface cable must be used in order to comply with the emission limits.

## Warning

This device complies with Part 15 of the FCC Rules.

Operation is subject to the following two conditions:

- (1) this device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

### Caution: Radio Frequency Radiation Exposure

This equipment complies with radio frequency exposure limits set forth by the FCC for an uncontrolled environment.

This equipment should be installed and operated with a minimum distance of 20 cm between the device and the user or bystanders.

### Co-Location

This device must not be co-located or operated in conjunction with any other antenna or transmitter.

## Brazil Information

Este equipamento não tem direito à proteção contra interferência prejudicial e não pode causar interferência em sistemas devidamente autorizados. Este equipamento não é apropriado para uso em ambientes domésticos, pois poderá causar interferências eletromagnéticas que obrigam o usuário a tomar medidas necessárias para minimizar estas interferências.

Para maiores informações, consulte o site da Anatel – <https://www.gov.br/anatel/pt-br/>

## Japan Information

当該機器には電波法に基づく、技術基準適合証明等を受けた特定無線設備を装着している。

## KCC Warning

이 기기는 사용 중 전파 혼신 가능성이 있으며, 타기기로부터 유해한 혼신을 받을 수 있음.

## Manufacturer/ importer

Testo SE & Co. KG aA  
Celsiusstr. 2, 79822 Titisee-Neustadt, Germany  
+49 7653 681-0  
[www.testo.com](http://www.testo.com)

Warning: Please follow the instructions when using the product.