

Mini data loggers for temperature and humidity

testo 174 T / testo 174 H with USB-C and PC software



Broad temperature measuring range from -22 to 158 °F (-30 °C to +70 °C)

Fast and simple data readout via USB-C

Professional software for Excel export, logger programming, data analysis and PDF reporting

Precise measurement of humidity and temperature in the range from -4 to 158 °F (-20 °C to +70 °C)

Reliable automatic data backup in the event of an empty battery or battery change; convenient storage of up to 16,000 measured values



testo 174 T BT / testo 174 H BT with Bluetooth and app connection



Broad temperature measuring range from -22 to 158 °F (-30 °C to +70 °C)

Free testoSmart App includes export function and report generation

Precise measurement of humidity and temperature in the range from -4 °F to 158 °F (-20 °C to +70 °C)

Simple and intuitive configuration as well as analysis of measurement data with the testo Smart App

Reliable automatic data backup in the event of an empty battery or battery change; convenient storage of up to 16,000 measured values



The testo 174 mini data loggers are perfect for commissioning, inspection, and maintenance of HVAC/R systems, as well as fault diagnosis and indoor climate monitoring. The testo 174 H and testo 174 H BT loggers measure temperature and humidity, while the testo 174 T and testo 174 T BT focus on temperature. All models store up to 16,000 values and protect against data loss with automatic backup during battery changes.

The free ComSoft Basic software allows quick setup and easy data analysis, including Excel export and PDF reports. ComSoft Professional provides advanced features for trend analysis, multi-location reports, and secure archiving.

Bluetooth models (174 H BT and 174 T BT) offer convenient operation via the testo Smart App, available for iOS and Android. The app lets you view measurements, create PDF reports, add photos/comments, and email results directly from your smartphone or tablet. These reliable, cost-effective loggers deliver precise data and support compliance with quality assurance standards.

The app allows you to create PDF reports and Excel exports, which can be enhanced with photos and comments, and easily sent via email from a smartphone or tablet.

Mini temperature data loggers

testo 174 T

testo 174 T mini temperature data logger with PC software, 1-channel, includes wall bracket, batteries (2 x CR2032 lithium) and test report



Order no. 0572 1740 02

USB-C





testo 174 T BT

testo 174 T BT mini temperature data logger with app connection, 1-channel, includes wall bracket, batteries (2 x CR2032 lithium) and test report



Order no. 0572 1742 02



	testo 174 T	testo 174 T BT
Sensor type	Digital	
Measuring range	-22 to 158 °F (-30 to +70 °C)	
Accuracy ±1 digit	±0.9 °F (-22 to 158 °F) (±0.5 °C (-30 to +70 °C))	
Resolution	0.1 °F / °C	
General technical data		
Channels	1 x internal	
Battery type	2 Lithium batteries (CR2032)	
Battery life	500 days (15 min. measuring cycle, 77 °F (+25 °C))	
Operating temperature	-22 to 158 °F (-30 to +70 °C)	
Storage temperature	-40 to 158 °F (-40 to +70 °C)	
Dimensions	2.4 X 1.5 X 0.7 in (60 X 38 X 18.5mm)	
Weight	1.2 oz (35g)	
Certification	EN12830	
Protection class	IP65	
Measuring cycle	1 min to 24 h	
Memory	16,000 readings	
Connection/connector	USB 2.0 / USB C	Bluetooth
Software	 testo ComSoft Basic testo ComSoft Professional	 testo Smart App
Logger configuration	✓	
Measurement data evaluation	✓	
Reporting	✓	✓ (only possible after registration)
Measurement data export	PDF / XLS / HTML / CSV	PDF / CSV / JSON

Mini data loggers for temperature and humidity

testo 174 H

testo 174 H mini data logger for temperature and humidity with PC software, 2-channel, includes wall bracket, batteries (2 x CR2032 lithium) and test report



Order no. 0572 1741 02

USB-C



testo 174 H BT

testo 174 H BT mini data logger for temperature and humidity with app connection, 2-channel, includes wall bracket, batteries (2 x CR2032 lithium) and test report





Order no. 0572 1743 02



	testo 174 H	testo 174 H BT
Sensor type	NTC	
Measuring range	-4 to 158 °F (-20 to +70 °C)	
Accuracy ±1 digit	±0.9 °F (-4 to 158 °F) (±0.5 °C (-20 to +70 °C))	
Resolution	0.1 °F / °C	
Sensor type	Testo humidity sensor, capacitive	
Measuring range	0 to 100 %RH*	
Accuracy ±1 digit	±3 %RH (2 to 98 %RH) ±0.03 %RH/K	
Resolution	0.1 %RH	


* Not for condensing atmospheres. For continuous application in high humidity (>80 %RH at ≤86 °F (30 °C) for >12 h, >60 %RH at >86 °F (30 °C) for >12 h), please contact us via our website.

General technical data		
Channels	2 x internal	
Battery type	2 Lithium batteries (CR2032)	
Battery life	1 year (15 min. measuring cycle, 77 °C (+25 °C))	
Operating temperature	-4 to 158 °F (-20 to +70 °C)	
Storage temperature	-40 to 158 °F (-40 to +70 °C)	
Dimensions	2.4 X 1.5 X 0.7 in (60 X 38 X 18.5mm)	
Weight	1.2 oz (35g)	
Protection class	IP20	
Measuring cycle	1 min to 24 h	
Memory	16,000 readings	
Connection/connector	USB 2.0	Bluetooth
Software	 testo ComSoft Basic testo ComSoft Professional	 testo Smart App
Logger configuration	✓	
Measurement data evaluation	✓	
Reporting	✓	✓ (only possible after registration)
Measurement data export	PDF / XLS / HTML / CSV	PDF / CSV / JSN

Accessories

ComSoft Basic

Basic software for programming and reading out Testo data loggers; display of measured values in graph and chart form, and export function.



Order no. 0572 0580



Free download

testo Smart App

The app turns your smartphone/tablet into the display for the testo 174 T BT / testo 174 H BT. Both the operation of the measuring instrument and the display of the readings are carried out via Bluetooth® through the testo Smart App on your smartphone or tablet – irrespective of measuring location. In addition, you can use the App to create measurement reports, add photos and comments to these and send them by e-mail. For iOS and Android.



Free download

ComSoft Professional

Professional software including data archiving for programming and reading out Testo data loggers and for other requirements such as merging measurement data generated at different locations.



Order no. 0554 1704



Accessories for all versions of testo 174


	Order no.
Lithium battery CR2032 button cell (please order 2 batteries per logger)	0515 5174
ISO temperature calibration certificate; calibration points -18 °C, 0 °C, +40 °C; per channel/instrument	0520 0153

Accessories for testo 174 T and testo 174 H

	Order no.
ComSoft Basic, basic software for programming and reading Testo data loggers; graphical and tabular display of readings, plus export function. Available as a download after registration.	0572 0580
ComSoft Professional, professional software, including data archiving	0554 1704

Accessories for testo 174 H and testo 174 H BT

	Order no.
ISO humidity calibration certificate; calibration points 11.3 %RH and 75.3 %RH at +25 °C/+77 °F; per channel/instrument	0520 0076



0981 0344/sab/10.2024

Subject to change, including technical modifications.