



testo 440

testo 400

General information		
Colour graphic display	✓	✓ HD display
Operation	Buttons	SmartTouch
Camera	–	✓ Rear camera: 8.0 MP Front camera: 5.0 MP
Magnets on the rear	✓	✓
Integrated differential pressure sensor	–	✓ High-precision and position-independent
Integrated absolute pressure sensor	–	✓
Compatible with the new Testo probe portfolio	✓ With cable 1x With Bluetooth® 1x	✓ With cable 2x With Bluetooth® 4x
Connection for Type K thermocouple	✓ 1x	✓ 2x
Intelligent calibration concept and digital probes	✓	✓
Zero-error display: Adjustment function at up to 6 measuring points	–	✓
Application support		
Graph curve	–	✓
Differential pressure measurement menu	–	✓
Differential temperature measurement menu	–	✓
Measurement data management		
Internal memory (number of measurement values)	✓ (225,000)	✓ (1,000,000)
Customer and measuring point management	–	✓
PC software for analyzing, archiving and documenting measurement data	–	✓
Personalized measurement protocols (including own logo)	–	✓
Integrated camera for documentation on site	–	✓
Onsite printing	✓	✓
Export formats	CSV via USB interface	CSV, PDF, JSON via PC software or directly from the measuring instrument (e-mail or Bluetooth)
Technical data		
Power supply	3x AAA	Li-ion/li-poly rechargeable battery
Dimensions	154 x 65 x 32 mm	210 x 95 x 39 mm
Weight	250 g	500 g