

A world class of its own.

Simply get started and hit the gas.
With the unbeatable tools for heating systems.



The world of Testo revolves – around your measurement tasks.

The times are changing. So are the challenges of installing and maintaining heating systems. That's why we at Testo think measurement technology further. From the single instrument to cross-application solutions. From analog to digital. From ever more complex requirements to ever simpler applications.

As the world market leader, we not only offer everything from a single source, but also everything fully

networked and digital. Get ready for a new world class of tools - and get them at a special promo price.

SECOND-SCREEN FUNCTION and easy documentation via testo Smart App

World class in flue gas measurement:

the testo 300 NEXT LEVEL

Why make measurements complicated when you can keep them simple? Good question. The best answer: The testo 300 NEXT LEVEL. Efficient, wireless and thanks to integrated BLUETOOTH® CONNECTOR for up to four additional parallel measurements. Intuitive documentation with the testo Smart App saves valuable time, paperwork and stress. Exhaust gas measurement can be this fast, simple and smart.



SMART-TOUCH DISPLAY: intuitive and

responsive

BLUETOOTH® CONNECTOR*:

4 further measurements in parallel via wireless Smart Probes









Simply get started and hit the gas: the testo 310 II.

The perfect start into the world of heating measurement technology: The new testo 310 II combines best-in-class efficiency and simplicity for the commissioning and maintenance of heating systems. You have everything in view on the individually configurable display and take up to 7 measurements simultaneously with the Testo Smart Probes. Flue gas measurement was never this efficient and simple.

SIMPLY DIGITAL: measure and document via testo Smart App

testo

- Flue gas measuring instrument testo 310 II for measuring O2, CO, hPa and °C
- Incl. lithium rech. battery for up to 8 hours of operation
- Incl. calibration protocol

Scope of delivery testo 310 II

- Free testo Smart App
- Optionally incl. printer

Order no. 0563 3104 (without printer) Order no. 0563 3105 (with printer)

INDIVIDUALLY
CONFIGURABLE
DISPLAY
shows all
measurements
at a glance

17,7 °C
13,4 %
12 ppm
6,1 %
33 ppm

4,31 % 93,9 % - 3,0 Pa

SMART DOCUMENTATION:

testo Smart App conveniently on smartphone or tablet

World class for temperature and differential pressure: the testo Smart Probes HVAC kit

Brand new on the market and already unbeatable: The testo Smart Probes HVAC kit offers everything you need for fast, flexible and wireless temperature and differential pressure measurements. Together with the testo Smart App, all measured values are sent directly to your smartphone or tablet and can be sent by e-mail from there in no time at all.



New!

cope of delivery

- testo 510i differential pressure measuring instrument with smartphone operation
- testo 915i thermometer with smartphone operation
- Air probe (TC Type K, Class 1)

testo 510i

- Immersion/penetration probe (TC Type K, Class 1)
- Surface probe (TC Type K, Class 1)
- Storage bag with batteries and calibration protocol
- Practical testo Smart Case
- Free testo Smart App

Order no. 0563 0010



testo Smart App for free download

NOW IN Google Play

Download at App Store



The whole world of modern heating measurement.



testo 300 NEXT LEVEL kits

	testo 300 kit 1	testo 300 kit 1 with printer	
Order no.	0564 3002 70	0564 3002 71	Per Ces \$\triangle \text{ Vacar or } \\ \tau \text{ Seminor } \text{ Seminor } \\ \tau \text{ Seminor } \text{ Seminor } \\ \tau \text{ Seminor } \\ \tau \text{ Seminor }
Instrument, including mains unit	O ₂ , CO, 4,000 ppm,	O ₂ , CO, 4,000 ppm,	Capita Continue Continue
Probe, including 10 spare filters	Compact flue gas probe (180 mm, Ø 6 mm)	Compact flue gas probe (180 mm, Ø 6 mm)	Tenn 108 407, 1 del 1 277, 1
Printer, including spare paper			19,0 ⁴ⁿ
testo EasyHeat PC software			
Instrument bag			testo 300
Smart Probes compatible			testo
Connection to Smart App			
Warranty	2 years	2 years	Illustration may differ from original.

testo	300 N	JEXT I	FVFI	Lonalife	kite

testo 300 NEXT LEVEL Longlife kits							
Order no.	testo 300 Longlife kit 1 0564 3004 70	testo 300 Longlife kit 1 with printer 0564 3004 71	testo 300 Longlife kit 2 0564 3004 82	testo 300 Longlife kit 2 with printer 0564 3004 89			
Instrument, including mains unit	O ₂ , CO, 4,000 ppm, NO, NO _{low} , CO _{low} sensor retrofittable	O ₂ , CO, 4,000 ppm, NO, NO _{low} , CO _{low} sensor retrofittable	${\rm O_2,~CO~H_2,~30,000~ppm,}$ ${\rm NO,~NO_{low},~CO_{low}}$ sensor retrofittable	${\rm O_2,\ CO\ H_2,\ 30,000\ ppm,}$ ${\rm NO,\ NO_{low},\ CO_{low}\ sensor}$ retrofittable			
Probe, including 10 spare filters	Compact flue gas probe (180 mm, Ø 6 mm)	Compact flue gas probe (180 mm, Ø 6 mm)	Modular flue gas probe (180 mm, Ø 8 mm)	Modular flue gas probe (180 mm, Ø 8 mm)			
Printer, including spare paper	-	~					
testo EasyHeat PC software							
Instrument case		<u> </u>					
Smart Probes compatible		✓					
Connection to Smart App		✓					
Warranty	4 years	4 years	4 years	4 years			



testo Bluetooth® Connector

testo Bluetooth® Connector for connecting the testo 300 flue gas analyzer to testo Smart Probes

0554 3004

For fast parallel measurements:

smartphone

the testo 310 II and the testo Smart Probes

Whether installation, maintenance or service - the new testo 310 II makes multi-tasking easier than ever. From temperature to differential pressure: With testo Smart Probes, you can even perform up to 6 measurements in parallel wirelessly.

Differential pressure measuring

instrument operated with your

For the measurement of differential

pressure on gas boilers, air flow

velocity and volume flow.

Order no. 0560 1510

Temperature kit

Immersion/penetration probe

Surface probe (all TC Type K,

Batteries and calibration protocol

Air probe

Class 1),

Stowing bag,

Order no. 0563 5915

SMART



Flue gas analyzer with individually configurable display

Simple and efficient for wireless maintenance and installation of heating systems and heat pumps - for up to 6 parallel measurements.

Order no. 0563 3104 (without printer) Order no. 0563 3105 (with printer)



testo 115i

Clamp thermometer operated via smartphone

Easy measurement of flow and return temperature, Bluetooth® range up to 100 m.

Order no. 0560 2115 02



For wireless temperature measurement in the most diverse applications thanks to large selection of probes and compatibility with common Type K thermocouple probes.

Order no. 0563 4915



testo Smart Probes

heating kit

Compact kit with three measuring instruments in robust testo Smart Case:

- testo 115i clamp thermometer
- testo 510i differential pressure
- measuring instrument testo 805i infrared thermometer
- Order no. 0563 0004 10



testo Smart Probes

complete kit

The ultimate kit for measuring temperature, humidity, flow velocity and pressure.

- clamp thermometer testo 115i
- high-pressure measuring instrument
- thermohygrometer testo 605i
- thermometer testo 905i
- infrared thermometer testo 805i
- thermal anemometer testo 405i
- x vane anemometer testo 410i x differential pressure measuring
- 1 x testo Smart Case



testo Smart Probes

HVAC kit

Compact kit for fast, flexible and wireless temperature and differential pressure measurements in robust testo Smart Case:

- testo 510i differential pressure measuring instrument
- testo 915i temperature kit
- Order no. 0563 0010



47.3-

40.8_{°c}

Smart digital manifolds with wireless clamp temperature probes and charging hose set in a practical case.

World class on heat pumps.



testo 570s





SMART


testo 557s Order no. 0564 5572







Order no. 0564 5503



Fully automatic and precise: Digital refrigerant scale with intelligent valve

testo 560i

Order no. 0564 2560

World class in leak detection.

Should not be missing in any refrigeration equipment: Testo leak detectors reliably locate all common refrigerants and, thanks to their high sensitivity, find even the smallest leaks quickly and reliably.



testo 316-3 **Leak detector** for refrigerants

- High sensitivity (< 4 g/a)
- Easiest operation with a single button

Order no. 0563 3163



testo 316-4 **Leak detector** for refrigerants

- Very high sensitivity (< 3 g/a)
- Visual and acoustic alarm for optimum leakage detection

Order no. 0563 3164

What else makes your world even better.



For the adjustment of air conditioning and ventilation systems, the monitoring of air quality or comfort measurements.

Order no. 0560 4402



testo 440 hot wire kit

For effortless measurement at air and ceiling vents.

OK

- testo 440 air velocity & IAQ measuring instrume
- Hot wire probe (Ø 9 mm) with fixed cable (length 1.7 m) including temperature sensor, with telescope (can be extended to 0.85 m)
- testo Smart Case

Order no. 0563 4400



Vane probe (Ø 100 mm)

Order no. 0635 9432

XXX.XX €



Extendable telescope

Order no. 0554 0960



testo 830-T2

infrared thermometer

With laser measurement spot marker for non-contact surface temperature measurement.

Order no. 0560 8312



testo 606-2 humidity measuring instrument

For recording wood and material moisture as well as air temperature and air humidity.

Order no. 0560 6062



testo 174 T kit Mini temperature data logger

For continuous temperature measurements, measurement data memory for 16,000 values, incl. mini data logger USB interface for programming and readout, and wall bracket.

Order no. 0572 0561



testo 174 H kit

Mini data logger

For continuous temperature and air humidity measurements, measurement data memory for 16,000 values, incl. mini data logger USB interface for programming and readout, and wall bracket.

Order no. 0572 0566



testo 770-3

clamp meter with Bluetooth®

- Get a good grip on cables even when things are tight. Easy to work with thanks to the fully retractable pincer arm
- Auto AC/DC and large two-line display
- Bluetooth connection to smartphone (with testo Smart Probes App)

Order no. 0590 7703





testo 760-2

digital multimeter

For measuring current, voltage and

- Automatic measurement parameter recognition
- Current measurement in the μA range
 True root mean square measurement

Order no. 0590 7602



testo 750-2

voltage tester

- Patented all-round LED display In accordance with DIN EN 61243-3:2011
- and CAT III With flashlight for measurement point illumination
- Including RC trigger function and vibrating load buttons

Order no. 0590 7502



non-contact voltage tester

- Adjustable for phase detection or voltage indication
- Visual and acoustic signal

Order no. 0590 7450



testo 925

Order no. 0563 0925

testo 922

0563 0922

Even more world class HVAC measuring instruments.

The professional tools for fast and precise measurement of temperature, humidity, flow velocity and volume flow - on gas heaters, heat pumps, hybrid and air conditioning systems.



0563 1625

testo 625

testo 417 kit

0563 1417



testo 535 0563 0535



differential pressure kit

Differential pressure measurement on gas boilers or on filters of air conditioning systems, and also flow measurements in ventilation ducts using a Pitot tube

Order no. 0563 0510



World class in thermography.

For checking radiators and underfloor heating, for detecting leaks and for the localization and function testing or pipes and lines the thermal imagers from Testo.



Order no. 0560 8650



testo 871 thermal imager

- Image quality with IR resolution of 240 x 180 pixels (480 x 360 with testo SuperResolution technology)
- Thermal sensitivity of 0.09 °C
- Wireless connection possible via Bluetooth probe for temperature and

Order no. 0560 8712



testo 872 thermal imager

testo 868 thermal imager

Image quality with IR resolution

Thermal sensitivity of 0.10 °C

report creation

Order no. 0560 8681

of 160 x 120 pixels (320 x 240 with testo SuperResolution technology)

Free analysis software and App for

- Image quality with IR resolution of 320 x 240 pixels (640 x 480 with testo SuperResolution technology)
- Thermal sensitivity of 0.06 °C
- Integrated laser marker can also be precisely visualized as a measuring point in the thermal image

Order no. 0560 8721



testo Thermography App

With the testo Thermography App, your smartphone/tablet becomes a second display, and a remote control for your thermal imager. In addition to this, you can use the App to create and send compact reports on site, and to save them online.



Welcome to the testo Smart World: The whole world in one App.

Faster, easier, smarter: The testo Smart App brings all tools and measurements together - and documentation can also be conveniently managed using a smartphone or tablet. Benefit from intelligent connectivity and the all-in-one solution for all applications. So that not only the jobs on all heating systems are dealt with smartly and effortlessly.



and IOS







World class services. With Testo.



We have the answers to your questions

If you need assistance with

certain measurement jobs, or if we can advise you on which measuring instrument is best suited to your application: Our experts are there for you.

Repair, service and instrument loans

So that you're always ready for action, we offer a 24-hour spare part service, including collection and delivery service as well as loan instrument service, for all Testo flue gas measuring instruments.

Calibration: More precision, more security

In our accredited laboratories, we ensure that your measuring technology works with precision and in compliance with the standards. From the first to the last measurement.



Even more measurement technology for heating systems

www.testo.com

