# Instructions Firmware-Update testo 340

1. Installation of the Testo instrument driver

To be able to communicate with the Testo measuring instruments, our device driver must be installed on your computer.

Follow these steps:

1. Open the folder **Firmware_Update_testo_340**

2. Start the program **USBDriver.exe** by double-clicking

3. Please confirm system messages to authorize the driver installation.

4. The installation of the drivers is started by clicking **Next**.

5. Then click **Finish** to complete this process.

Instructions Firmware-Update testo 340

2. Firmware Update testo 340

Follow these steps:

1. Switch testo 340 off and unplug the power supply

2. [▲] keep pressed down

3. Plug in the power adapter, [▲] keep pressed.

   → The testo 340 beeps and the red LEDs of the condensate trap are flashing
   → No indication on the display

4. [▲] let go

5. Insert the USB connection cable (0449 0047) into the USB socket of the testo 340 and connect it to the PC.

6. Open the folder **Firmware_Update_testo_340**

7. Start the program **USBFlashUpdate** by double-clicking

8. Click **Browse** in the new window

Instructions Firmware-Update testo 340

9. In the **Firmware_Update_testo_340** folder, select the **t340rel.bin** file and click **Open**

10. Select the following settings:

    a. **USB Device:**   **testo 340**

    b. **Baudrate:**   **921600**

11. Click **Start** to start the firmware update of the testo 340

12. Click on **OK** to confirm the successful firmware update of the testo 340

13. Then close the "Testo USB Flash Update" program by clicking **Close**